



Colline

Design Frans Dijkmeijer

Composition: 75% new wool, 17% acrylic, 8% nylon

Yarn type: Worsted

Binding: Plain weave

Width: 140 cm

Weight: Approximately 650 g/lin.m

Repeat: None

Cleaning: Dry cleaning or cleaning with foam detergents.

Stain removal: See special guide.

Colline

Abrasion

Approximately 100.000 rubs according to the Martindale method
EN ISO 12947

Pilling

Note 4-5, EN ISO 12945

Lightfastness

Note 6, ISO 105-B02

Flame resistance

EN 1021-1/2
DIN 4102 B2
NF D 60 013
UNI 9175, 1IM
US Cal. Tech. Bull. 117
IMO A.652(16)

Crib 5 when flameprotected

No use of brominated flameretardants

Quality benefits

Very good abrasion

Very good lightfastness

Flameretardant

Environmental benefits

Wool is a renewable resource

Wool is biodegradable

Wool is flameretardant

Wool is naturally soil resistant

Wool is very comfortable, because of its ability to absorb/give off humidity

Wool ages with grace.

No use of AZO dyes, which may split off carcinogenic acrylamines

No use of dyes containing heavy metals/complies with ETAD norm

No content of formaldehyde

Biodegradable spinning oil

Complies with REACH Regulation

No use of brominated flameretardants if treated

Images can be downloaded at
www.kvadrat.dk/company/press_room

For further information
www.kvadrat.dk