

Light source

mod. A
LED board 24V DC / 7x6W / energy class A+ / lumen 4410 / K range 2600-2800 / CRI 80

mod. B
LED board 24V DC / 2x6W / energy class A+ / lumen 1260 / K range 2600-2800 / CRI 80

mod. C
LED board 24V DC / 7x6W / energy class A+ / lumen 4410 / K range 2600-2800 / CRI 80

mod. D
LED board 24V DC / 10x6W / energy class A+ / lumen 6300 / K range 2600-2800 / CRI 80

mod. E
LED board 24V DC / 4x6W / energy class A+ / lumen 2520 / K range 2600-2800 / CRI 80

mod. F
LED board 24V DC / 9x6W / energy class A+ / lumen 5670 / K range 2600-2800 / CRI 80

mod. I
LED board 24V DC / 5x6W / energy class A+ / lumen 3150 / K range 2600-2800 / CRI 80


Power supply


low voltage driver 24V DC 220-240V dimmable Triac (dimmable 1...10V or DALI version available on request)?
(110V available on request)

Dimensions

rods H 145 cm variable (on request 300 cm)


base Ø 21x10,5 H cm

 mod. D discs
Ø 120-80-50-30-18 cm
weight 16 kg

 mod. A
discs Ø 80-50-30-18 cm
weight 10 kg

—
mod. B
discs Ø 80-18 cm
weight 6 kg

—
mod. C
discs Ø 120-80-50 cm
weight 13 kg

 mod. E
discs Ø 50-30-18 cm
weight 6 kg

—
mod. F
discs Ø 120-80-50-30 cm
weight 15 kg

—
mod. I
discs Ø 80-50-30 cm
weight 8 kg

Order code mod. A MALG gold
MALS silver
MALC copper

Order code mod. B MBLG gold
MBLS silver
MBLC copper

Order code mod. C MCLG gold
MCLS silver
MCLC copper

Order code mod. D MDLG gold
MDLS silver
MDLC copper

Order code mod. E MELG gold
MELS silver
MELC copper

Order code mod. F MFLG gold
MFLS silver
MFLC copper

Order code mod. I MILG gold
MILS silver
MILC copper
