

m o o o i

## Perch Light Branch

UMUT YAMAC



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life? We all recognize this image and steal a moment from our precious time to admire this triumph of nature and beauty.

---

### *Detailing*



These sunlit birds are free to swing when softly touched. They gently glow and bring along the promise of spring.

---

### *Colours*

Brass and white


---

# Perch Light Branch / Large

## Dimensions

112cm | 44.1"

41cm | 16.1"



53cm | 20.9"

## Product

**WIDTH** 112cm | 44.1"

**HEIGHT** 53cm | 20.9"

**DEPTH** 41cm | 16.1"

**WEIGHT NETTO** 9kg | 19.84lbs

## Packaging

**WIDTH** 34cm | 13.4"

**HEIGHT** 53cm | 20.9"

**CUBAGE** 0.21m<sup>3</sup> | 7.32ft<sup>3</sup>

**LENGTH** 115cm | 45.3"

**WEIGHT** 9kg | 19.84lbs

## Technical CE

### ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

### MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

5

### SHAPE

Linear

### INPUT VOLTAGE

180-240

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

15W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

3000 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

560 lm

## Technical cULus

### ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

### MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

5

### SHAPE

Linear

### INPUT VOLTAGE

90-305

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

20W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

3000 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

560 lm

## Perch Light Branch / Small

### Dimensions

73cm | 28.7"



24cm | 9.5"



4cm | 1.6"



53cm | 20.9"



36cm | 14.2"

> 118cm | 46.5"



157cm | 61.8"

### Product

**WIDTH** 73cm | 28.7"

**HEIGHT** 53cm | 20.9"

**DEPTH** 36cm | 14.2"

**WEIGHT NETTO** 7kg | 15.43lbs

### Packaging

**WIDTH** 36cm | 14.2"

**HEIGHT** 41cm | 16.1"

**CUBAGE** 0.14m<sup>3</sup> | 4.85ft<sup>3</sup>

**LENGTH** 93cm | 36.6"

**WEIGHT** 7kg | 15.43lbs

## Technical CE

### ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

### MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

### ENERGY LABEL

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

3

### SHAPE

Linear

### INPUT VOLTAGE

100-240

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

15W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Matching steel cylinder

### COLOUR TEMPERATURE

3000 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

336 lm

---

## Technical cULus

### ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

### MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

### ENERGY LABEL

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

3

### SHAPE

Linear

### INPUT VOLTAGE

90-264

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

20W

**DIMMABLE**

Yes

**LIFETIME**

50000 hours

**CABLE LENGTH**

1000cm | 393.7"; 400cm | 157.5"

**COLOUR TEMPERATURE**

3000 K

**LIGHT DIRECTION**

All directions

**LAMPHOLDER**

LED (Solid state)

**CABLE COLOUR**

Black

**CANOPY**

Matching steel cylinder

**CRI**

80

**LIGHT OUTPUT**

336 lm

---

## *Dimmer*

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

**DIMMER TYPE**

1-10V

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

---