

m o o o i

Starfall Light

FRONT



Live under the stars with Starfall Light by Front! The Starfall Light is a circular suspension light with a contemporary twist. Punctuated with 30 LED light sources, this upside-down chandelier brings perpetual star fall in your home. Thanks to 30 slim arms of different lengths, it not only resembles falling stars but also a starry night sky with dots of light at varying heights. A brand-new constellation waiting to be discovered! Installation is a breeze, thanks to the arms already in place, so you can enjoy your falling stars within moments.

Detailing



With the Starfall Light, you can go to sleep under the stars every night. Or dine with the watchful stars above you.


Colours



Black

Starfall Light / 30

Dimensions



Product

WIDTH 105cm | 41.3"
HEIGHT 50cm | 19.7"
DEPTH 105cm | 41.3"
DIAMETER 105cm | 41.3"
WEIGHT NETTO 2.9kg | 6.39lbs

Packaging

WIDTH 64cm | 25.2"
HEIGHT 30cm | 11.8"
CUBAGE 0.22m³ | 7.8ft³
LENGTH 115cm | 45.3"
WEIGHT 5kg | 11.02lbs

Technical CE / UL

MATERIAL
Powdercoated Stainless Steel and Poly Carbonate

INSTALLATION REQUIRED
Yes

LIGHTSOURCE INCLUDED
Yes

INPUT VOLTAGE
110-270V

MAX POWER CONSUMPTION
15W

LIFETIME
50000 hours

CABLE LENGTH
1000cm | 393.7"; 250cm | 98.4"

COLOUR TEMPERATURE
2700 K

LIGHT OUTPUT
1200 lm

EEI
0.17

MEASURED POWER CONSUMPTION
22W

LIGHTSOURCE TYPE
LED

NUMBER OF LIGHTSOURCES
30

FREQUENCY
50/60

LAMPHOLDER
LED (Solid state)

CABLE COLOUR
Black

CANOPY
Pebble III Black, ABS

CRI
91

CONSTANT CURRENT / CONSTANT VOLTAGE
Constant current

EFFICIENCY
80 lm/W

OUTPUT CURRENT
660 mL

OUTPUT VOLTAGE

22,3V

DRIVER TYPE

EldoLED

DIMMING & LIGHTING CONTROL

DALI dt6, Wireless Wall Switch, Push / Pulse dim on
Line Voltage

See last page for more information about the dimming possibilities.



*Energy Label information***TYPE OF LIGHT SOURCE**

LED

LIGHTING TECHNOLOGY USED

LED

TYPE OF LIGHT SOURCE

DLS

LAMPHOLDER

LED (Solid state)

COLOUR-TUNEABLE LIGHT SOURCE

No

DIMMABLE

Yes

ENERGY CONSUMPTION IN ON-MODE (KWH/1000 H)

15 kWh

ENERGY EFFICIENCY CLASS

G

USEFUL LUMINOUS FLUX (ΦUSE)

1200 lm

CORRELATED COLOUR TEMPERATURE

2700 K

ON-MODE POWER (PON)

15W

LIFETIME

50000 hours

**COLOUR RENDERING INDEX, ROUNDED TO THE NEAREST INTEGER, OR
THE RANGE OF CRI-VALUES THAT CAN BE SET**

91

**BEAM ANGLE IN DEGREES, OR THE RANGE OF BEAM ANGLES THAT CAN
BE SET**

27

CHROMATICITYx: 0.4578; y: 0.4044

Dimming & Lighting Control

DALI dt6

The luminaire is dimmable by integrating it into a DALI network. This is an universal and professional standard in home automation systems with endless control possibilities and ease. We advise to hire a professional to integrate the luminaire into your DALI network.

Compatible models: 30 CE, 30 UL

Wireless Wall Switch

With our Wireless Wall Switch, you'll have full control over your Moooi lighting design with one touch. Our Wireless Wall Switch comprises two components, a wall switch and radio device to put in the canopy of your Moooi lighting design. The wall switch can be integrated in System 55 or Decora style wall switches. The Wireless Wall Switch communicates via Bluetooth with the radio device in the luminaires canopy. Within moments you can enjoy full and fluent dimming, all the way to dark.

Compatible models: 30 CE, 30 UL

Push / Pulse dim on Line Voltage

The luminaire is dimmable by using an external momentary switch or pushbutton switch. The switch is usually mounted on an existing wall socket. In some cases a Phase or Control wire needs to be added to your home's wiring. The switch should be suitable for use with line voltage and of the type 'normal off - momentary on'. The luminaire dims perfectly when the switch makes and holds contact. A short press switches between on and off.

Compatible models: 30 CE, 30 UL
