



Ripple

Design: Kinnasand

Type: Curtain

Composition: 90% Trevira CS, 10% polyester FR

Yarn type: Filament

Binding: Jacquard

Width: Approx. 286 cm, 112.5 inches

Weight: Approx. 150 g/lin.m, 4.8 oz/ly

Repeat: None

Colour difference may occur

Cleaning: Washing at max. 60°C.

Drip drying.

Shrinkage approx. 1% / 0% when washed at 60°C.

Ironing might be necessary

Disinfection, see www.kvadrat.dk

More info: Care and maintenance [kvadrat.dk](http://www.kvadrat.dk)



10 year
warranty



Ripple

Lightfastness

Note 3-7 ISO 105-B02

Flame resistance

CAN ULC S102

CAN ULC S109

DIN 4102 B1

NF P 92 507 M1

NFPA 701

ACT Guidelines Woven fabrics

Flammability

NFPA 701

Dry & Wet Crocking AATCC 8

Dry Crocking: Grade 5.0

Wet Crocking: Grade 5.0

Colour Fastness to Light AATCC 16

Grade 4.0 minimum 60 hours

Physical properties

Seam Slippage warp 11.5 / weft 15 lbs. (Fail) ASTM D434

Seam Slippage ASTM D434

Quality benefits

Permanent flame retardant

Washable

Environmental benefits

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

Mono-material designed for circularity

Recyclable

Green Building certificates

Greenguard Gold: Low chemical emission

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

Italy

Warranty

10 years. See terms and conditions on www.kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

Kvadrat A/S is ISO 9001 and ISO 14001 certified

For further information

kvadrat.dk